

# DTD documentation

## Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1 .....	4
3.2 .....	4
3.3 .....	5
3.4 .....	5
3.5 .....	5
3.6 .....	6
3.7 .....	6
3.8 .....	7
3.9 .....	7
3.10 .....	8
3.11 .....	8
3.12 .....	8
3.13 .....	9
3.14 .....	9
3.15 .....	10
3.16 .....	10
3.17 .....	10
3.18 .....	11
3.19 .....	11
3.20 .....	11
3.21 .....	12
3.22 .....	12
3.23 .....	13
3.24 .....	13
3.25 .....	13
3.26 .....	14
3.27 .....	14
3.28 .....	14

3.29 .....	15
3.30 .....	15
3.31 .....	16
3.32 .....	16
3.33 .....	16
3.34 .....	17
3.35 .....	17
3.36 .....	17
3.37 .....	18
3.38 .....	18
3.39 .....	18
3.40 .....	18
3.41 .....	19
3.42 .....	19
3.43 .....	19
3.44 .....	20
3.45 .....	20
3.46 .....	20
3.47 .....	21
3.48 .....	21
3.49 .....	21
3.50 .....	22
3.51 .....	22
3.52 .....	22
3.53 .....	22
3.54 .....	23
3.55 .....	23
3.56 .....	23
3.57 .....	24
3.58 .....	24
3.59 .....	24
3.60 .....	25
3.61 .....	25
3.62 .....	26

## 1. Top-level element(s)

---

- [document](#)
- [howto](#)
- [overview](#)

## 2. List of elements

---

- [a](#)
- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [area](#)
- [audience](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [elaboration](#)
- [em](#)
- [extension](#)
- [faq](#)
- [faqs](#)
- [faqsection](#)
- [feedback](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [header](#)
- [howto](#)
- [icon](#)
- [img](#)
- [last-modified-content-date](#)
- [legal](#)
- [li](#)
- [map](#)
- [meta](#)
- [note](#)
- [notice](#)
- [ol](#)
- [overview](#)
- [p](#)
- [person](#)

- [prerequisites](#)
- [purpose](#)
- [question](#)
- [references](#)
- [section](#)
- [source](#)
- [steps](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)
- [table](#)
- [td](#)
- [th](#)
- [tips](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

### 3. Element declarations

#### 3.1.

person		
Content model	EMPTY	
Attributes	id	ty
	class	ty
	xml:lang	ty
	name	ty r
	email	ty r
Used inside	<a href="#">authors</a>	

#### 3.2.

strong	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *

Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.3.

em			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   a ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.4.

code			
Content model	( #PCDATA )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.5.

sup										
Content model	( #PCDATA )									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>									

### 3.6.

sub										
Content model	( #PCDATA )									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>									

### 3.7.

a																
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a> ) *															
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> <tr> <td>href</td> <td></td> <td>ty r</td> </tr> <tr> <td>title</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty	href		ty r	title		ty
id		ty														
class		ty														
xml:lang		ty														
href		ty r														
title		ty														

Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>

### 3.8.

br		
Content model	EMPTY	
Attributes	id	
	class	
	xml:lang	
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

### 3.9.

img		
Content model	EMPTY	
Attributes	src	
	alt	
	height	
	width	
	usemap	
	ismap	
	id	
	class	
xml:lang		
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>	

### 3.10.

map	
Content model	( <a href="#">area</a> + )
Attributes	name
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>

### 3.11.

area	
Content model	EMPTY
Attributes	shape coords href title nohref alt
Used inside	<a href="#">map</a>

### 3.12.

icon	
Content model	EMPTY
Attributes	src alt height width

	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.13.

acronym			
Content model	(#PCDATA) *		
Attributes	title		ty
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>   <a href="#">elaboration</a>   <a href="#">answer</a>		

### 3.14.

p			
Content model	(#PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
	xml:space		p p
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.15.

source	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *
Attributes	id
	class
	xml:lang
	xml:space
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.16.

note	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *
Attributes	label
	id
	class
	xml:lang
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.17.

warning	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *
Attributes	label

	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.18.

fixme			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		
Attributes	author		ty
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.19.

table			
Content model	( <a href="#">caption</a> ? , <a href="#">tr</a> + )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.20.

caption	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">table</a>

### 3.21.

tr	
Content model	( <a href="#">th</a>   <a href="#">td</a> ) +
Attributes	id
	class
	xml:lang
Used inside	<a href="#">table</a>

### 3.22.

th	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	id
	class
	xml:lang
	colspan
	rowspan
Used inside	<a href="#">tr</a>

### 3.23.

td	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	id
	class
	xml:lang
	colspan
	rowspan
Used inside	<a href="#">tr</a>

### 3.24.

li	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">ul</a>   <a href="#">ol</a>

### 3.25.

ul	
Content model	( <a href="#">li</a> ) +
Attributes	id
	class
	xml:lang

	spacing		p c
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.26.

ol			
Content model	( <a href="#">li</a> ) +		
Attributes	id		ty
	class		ty
	xml:lang		ty
	spacing		p c
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.27.

dl			
Content model	( <a href="#">dt</a> , <a href="#">dd</a> ) +		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.28.

dt			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *		

Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">dl</a>		

### 3.29.

dd			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">dl</a>		

### 3.30.

figure			
Content model	EMPTY		
Attributes	src		ty r
	alt		ty r
	height		ty
	width		ty
	usemap		ty
	ismap		p
	align		ty
	id		ty
	class		ty
xml:lang		ty	

Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.31.

anchor	
Content model	EMPTY
Attributes	id
	class
	xml:lang
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.32.

document	
Content model	( <a href="#">header</a> , <a href="#">body</a> , <a href="#">footer</a> ? )
Attributes	id
	class
	xml:lang

### 3.33.

header	
Content model	( <a href="#">title</a> , <a href="#">subtitle</a> ? , <a href="#">version</a> ? , <a href="#">type</a> ? , <a href="#">authors</a> ? , <a href="#">notice</a> * , <a href="#">abstract</a> ? , <a href="#">meta</a> * , <a href="#">last-modified-content-date</a> )
Attributes	id
	class
	xml:lang
Used inside	<a href="#">document</a>   <a href="#">howto</a>

### 3.34.

title	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">a</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">header</a>   <a href="#">section</a>   <a href="#">faqs</a>   <a href="#">faqsection</a>

### 3.35.

subtitle	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">header</a>

### 3.36.

version	
Content model	( #PCDATA )
Attributes	id
	class
	xml:lang
	major
	minor
	fix
	tag
Used inside	<a href="#">header</a>

--

### 3.37.

type	
Content model	( #PCDATA )
Attributes	
id	
class	
xml:lang	
Used inside	
	<a href="#">header</a>

### 3.38.

authors	
Content model	( <a href="#">person</a> + )
Attributes	
id	
class	
xml:lang	
Used inside	
	<a href="#">header</a>   <a href="#">faqs</a>

### 3.39.

notice	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *
Attributes	
id	
class	
xml:lang	
Used inside	
	<a href="#">header</a>

### 3.40.

abstract										
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">header</a>									

### 3.41.

meta													
Content model	( #PCDATA )												
Attributes	<table border="1"> <tr> <td>name</td> <td></td> <td>ty</td> </tr> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	name		ty	id		ty	class		ty	xml:lang		ty
name		ty											
id		ty											
class		ty											
xml:lang		ty											
Used inside	<a href="#">header</a>												

### 3.42.

body										
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) +									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">document</a>									

### 3.43.

section										
Content model	( <a href="#">title</a> , ( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) * )									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">prerequisites</a>   <a href="#">steps</a>   <a href="#">tips</a>   <a href="#">references</a>									

**3.44.**

footer	
Content model	( <a href="#">legal</a> )
Used inside	<a href="#">document</a>

**3.45.**

legal										
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">footer</a>									

**3.46.**

faqs										
Content model	( <a href="#">title</a> ? , <a href="#">authors</a> ? , ( <a href="#">faq</a>   <a href="#">faqsection</a> ) + )									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								

Used inside	<a href="#">howto</a>

### 3.47.

faqsection										
Content model	( <a href="#">title</a> , ( <a href="#">faq</a>   <a href="#">faqsection</a> ) + )									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">faqs</a>   <a href="#">faqsection</a>									

### 3.48.

faq										
Content model	( <a href="#">question</a> , <a href="#">answer</a> )									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">faqs</a>   <a href="#">faqsection</a>									

### 3.49.

question										
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">elaboration</a> ) *									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">faq</a>									

**3.50.**

elaboration										
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a> ) *									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">question</a>									

**3.51.**

answer				
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">map</a>   <a href="#">a</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *			
Attributes	<table border="1"> <tr> <td>author</td> <td></td> <td>ty</td> </tr> </table>	author		ty
author		ty		
Used inside	<a href="#">faq</a>			

**3.52.**

howto										
Content model	( <a href="#">header</a> , <a href="#">audience</a> ? , <a href="#">purpose</a> ? , <a href="#">prerequisites</a> ? , <a href="#">steps</a> , <a href="#">extension</a> ? , <a href="#">faqs</a> ? , <a href="#">tips</a> ? , <a href="#">references</a> ? , <a href="#">feedback</a> ? )									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								

**3.53.**

overview	
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *

Attributes	title		ty r
	id		ty
	class		ty
	xml:lang		ty

### 3.54.

purpose			
Content model	( p   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	title		ty r
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">howto</a>		

### 3.55.

prerequisites			
Content model	( <a href="#">section</a>   p   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	title		ty r
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">howto</a>		

### 3.56.

audience			
Content model	( p   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		

Attributes	title		ty r
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">howto</a>		

### 3.57.

steps			
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	title		ty r
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">howto</a>		

### 3.58.

extension			
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	title		ty r
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">howto</a>		

### 3.59.

tips	
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	class
	xml:lang
Used inside	<a href="#">howto</a>

### 3.60.

references	
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	class
	xml:lang
Used inside	<a href="#">howto</a>

### 3.61.

feedback	
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	class
	xml:lang

Used inside	<a href="#">howto</a>

**3.62.**

last-modified-content-date		
Content model	EMPTY	
Attributes	date	
Used inside	<a href="#">header</a>	