

# DTD documentation

## Table of contents

1 Top-level element(s).....	3
2 List of elements.....	3
3 Element declarations.....	4
3.1 .....	4
3.2 .....	4
3.3 .....	5
3.4 .....	5
3.5 .....	5
3.6 .....	6
3.7 .....	6
3.8 .....	7
3.9 .....	7
3.10 .....	7
3.11 .....	8
3.12 .....	8
3.13 .....	9
3.14 .....	9
3.15 .....	10
3.16 .....	10
3.17 .....	10
3.18 .....	11
3.19 .....	11
3.20 .....	12
3.21 .....	12
3.22 .....	12
3.23 .....	13
3.24 .....	13
3.25 .....	13
3.26 .....	14
3.27 .....	14
3.28 .....	14

3.29 .....	15
3.30 .....	15
3.31 .....	16
3.32 .....	16
3.33 .....	16
3.34 .....	17
3.35 .....	17
3.36 .....	17
3.37 .....	18
3.38 .....	18
3.39 .....	18
3.40 .....	19
3.41 .....	19
3.42 .....	19
3.43 .....	20
3.44 .....	20
3.45 .....	20
3.46 .....	20
3.47 .....	21
3.48 .....	21
3.49 .....	21
3.50 .....	22
3.51 .....	22
3.52 .....	22
3.53 .....	23
3.54 .....	23
3.55 .....	23
3.56 .....	24
3.57 .....	24
3.58 .....	24
3.59 .....	25
3.60 .....	25

## 1. Top-level element(s)

---

- [document](#)
- [howto](#)
- [overview](#)

## 2. List of elements

---

- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [audience](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [em](#)
- [extension](#)
- [faq](#)
- [faqs](#)
- [feedback](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [fork](#)
- [header](#)
- [howto](#)
- [icon](#)
- [img](#)
- [jump](#)
- [last-modified-content-date](#)
- [legal](#)
- [li](#)
- [link](#)
- [note](#)
- [notice](#)
- [ol](#)
- [overview](#)
- [p](#)
- [part](#)
- [person](#)
- [prerequisites](#)
- [purpose](#)

- [question](#)
- [references](#)
- [section](#)
- [source](#)
- [steps](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)
- [table](#)
- [td](#)
- [th](#)
- [tips](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

### 3. Element declarations

#### 3.1.

person		
Content model	EMPTY	
Attributes	id	type
	class	type
	xml:lang	type
	name	type required
	email	type required
Used inside	<a href="#">authors</a>	

#### 3.2.

strong		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	id	type

	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

### 3.3.

em			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

### 3.4.

code			
Content model	( #PCDATA )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

### 3.5.

sup			
Content model	( #PCDATA )		

Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

**3.6.**

sub			
Content model	( #PCDATA )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

**3.7.**

link			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
	href		ty r
	role		ty
	title		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

### 3.8.

jump	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *
Attributes	id
	class
	xml:lang
	href
	role
	title
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>

### 3.9.

fork	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *
Attributes	id
	class
	xml:lang
	href
	role
	title
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>

### 3.10.

br	
----	--

Content model		EMPTY
Attributes		
	id	
	class	
	xml:lang	
Used inside		
	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>	

### 3.11.

img		
Content model		EMPTY
Attributes		
	src	
	alt	
	height	
	width	
	usemap	
	ismap	
	id	
	class	
	xml:lang	
Used inside		
	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>	

### 3.12.

icon		
Content model		EMPTY
Attributes		
	src	
	alt	

	height		ty
	width		ty
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

### 3.13.

acronym			
Content model	( #PCDATA ) *		
Attributes	title		ty
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>		

### 3.14.

p			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
	xml:space		p p

Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.15.

source	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	id
	class
	xml:lang
	xml:space
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.16.

note	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	label
	id
	class
	xml:lang
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.17.

warning
---------

Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	label	
	id	
	class	
	xml:lang	
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.18.

fixme		
Content model		( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	author	
	id	
	class	
	xml:lang	
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.19.

table		
Content model		( <a href="#">caption</a> ? , <a href="#">tr</a> + )
Attributes	id	
	class	
	xml:lang	
Used inside		<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

--

### 3.20.

caption	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">table</a>

### 3.21.

tr	
Content model	( <a href="#">th</a>   <a href="#">td</a> ) +
Attributes	id
	class
	xml:lang
Used inside	<a href="#">table</a>

### 3.22.

th	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	id
	class
	xml:lang
	colspan
	rowspan

Used inside	<a href="#">tr</a>

### 3.23.

td	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	id
	class
	xml:lang
	colspan
	rowspan
Used inside	<a href="#">tr</a>

### 3.24.

li	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">ul</a>   <a href="#">ol</a>

### 3.25.

ul	
Content model	( <a href="#">li</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a> ) +
Attributes	id

	class		ty
	xml:lang		ty
	spacing		p c
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.26.

ol			
Content model	( <a href="#">li</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a> ) +		
Attributes	id		ty
	class		ty
	xml:lang		ty
	spacing		p c
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.27.

dl			
Content model	( <a href="#">dt</a> , <a href="#">dd</a> ) +		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.28.

dt	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">dl</a>

### 3.29.

dd	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	id
	class
	xml:lang
Used inside	<a href="#">dl</a>

### 3.30.

figure	
Content model	EMPTY
Attributes	src
	alt
	height
	width
	usemap
	ismap
	align

	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.31.

anchor			
Content model	EMPTY		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dd</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>		

### 3.32.

document			
Content model	( <a href="#">header</a> , <a href="#">body</a> , <a href="#">footer</a> ? )		
Attributes	id		ty
	class		ty
	xml:lang		ty

### 3.33.

header			
Content model	( <a href="#">title</a> , <a href="#">subtitle</a> ? , <a href="#">version</a> ? , <a href="#">type</a> ? , <a href="#">authors</a> ? , <a href="#">notice</a> * , <a href="#">abstract</a> ? , <a href="#">last-modified-content-date</a> )		
Attributes	id		ty
	class		ty

	xml:lang		ty
Used inside	<a href="#">document</a>   <a href="#">howto</a>		

### 3.34.

title			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">header</a>   <a href="#">section</a>   <a href="#">part</a>		

### 3.35.

subtitle			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">header</a>		

### 3.36.

version			
Content model	( #PCDATA )		
Attributes	id		ty
	class		ty
	xml:lang		ty
	major		ty
	minor		ty

	fix		ty
	tag		ty
Used inside	<a href="#">header</a>		

### 3.37.

type			
Content model	( #PCDATA )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">header</a>		

### 3.38.

authors			
Content model	( <a href="#">person</a> + )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">header</a>   <a href="#">faqs</a>		

### 3.39.

notice			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty

Used inside	<a href="#">header</a>

### 3.40.

abstract										
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">header</a>									

### 3.41.

body										
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) +									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">document</a>									

### 3.42.

section										
Content model	( <a href="#">title</a> , ( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) * )									
Attributes	<table border="1"> <tr> <td>id</td> <td></td> <td>ty</td> </tr> <tr> <td>class</td> <td></td> <td>ty</td> </tr> <tr> <td>xml:lang</td> <td></td> <td>ty</td> </tr> </table>	id		ty	class		ty	xml:lang		ty
id		ty								
class		ty								
xml:lang		ty								
Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">prerequisites</a>   <a href="#">steps</a>   <a href="#">tips</a>   <a href="#">references</a>									

--

### 3.43.

footer	
Content model	( <a href="#">legal</a> )
Used inside	<a href="#">document</a>

### 3.44.

legal		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	id	ty
	class	ty
	xml:lang	ty
Used inside	<a href="#">footer</a>	

### 3.45.

faqs		
Content model	( <a href="#">authors</a> ? , ( <a href="#">faq</a>   <a href="#">part</a> ) + )	
Attributes	id	ty
	class	ty
	xml:lang	ty
	title	ty r
Used inside	<a href="#">howto</a>	

### 3.46.

part	
Content model	( <a href="#">title</a> , ( <a href="#">faq</a>   <a href="#">part</a> ) + )

Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">faqs</a>   <a href="#">part</a>		

### 3.47.

faq			
Content model	( <a href="#">question</a> , <a href="#">answer</a> )		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">faqs</a>   <a href="#">part</a>		

### 3.48.

question			
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *		
Attributes	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">faq</a>		

### 3.49.

answer			
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	author		ty

Used inside	<a href="#">faq</a>

### 3.50.

howto	
Content model	( <a href="#">header</a> , <a href="#">audience</a> ? , <a href="#">purpose</a> ? , <a href="#">prerequisites</a> ? , <a href="#">steps</a> , <a href="#">extension</a> ? , <a href="#">faqs</a> ? , <a href="#">tips</a> ? , <a href="#">references</a> ? , <a href="#">feedback</a> ? )
Attributes	id
	class
	xml:lang

### 3.51.

overview	
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	class
	xml:lang

### 3.52.

purpose	
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	class
	xml:lang
Used inside	<a href="#">howto</a>

### 3.53.

prerequisites	
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	class
	xml:lang
Used inside	<a href="#">howto</a>

### 3.54.

audience	
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	class
	xml:lang
Used inside	<a href="#">howto</a>

### 3.55.

steps	
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	class
	xml:lang

Used inside	<a href="#">howto</a>

### 3.56.

extension	
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	class
	xml:lang
Used inside	<a href="#">howto</a>

### 3.57.

tips	
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	class
	xml:lang
Used inside	<a href="#">howto</a>

### 3.58.

references	
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id

	class		ty
	xml:lang		ty
Used inside	<a href="#">howto</a>		

### 3.59.

feedback			
Content model	( p   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	title		ty
	id		ty
	class		ty
	xml:lang		ty
Used inside	<a href="#">howto</a>		

### 3.60.

last-modified-content-date			
Content model	EMPTY		
Attributes	date		ty
Used inside	<a href="#">header</a>		